

Luminaire

Code BB11000+DV1015
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W ND

Measurem.

Code FTS1801149
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W ND


Luminaire Flux	4388.60 lm	Luminaire Power	54.00 W	Efficacy	81.27 lm/W	Efficiency	100.00%
Sources Flux	4388.60 lm	Maximum value	1117.04 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	188 mm	Width	188 mm	Height	238 mm
Rectangular Luminous Area		Length	177 mm	Width	177 mm	Height	0 mm
Horizontal Luminous Area		0.031329 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007579 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4388.60 lm	

LED Flux=5451lm LED Power=50W Eff=81% EfcLed=109lm/W EfcLum=81lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h


C.I.E. 95 100 100 100 100
 F UTE 1.00 A

D DIN 5040
 B NBN

A60
 BZ 1



ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code BB11000+DV1015
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W ND

Measurerm.


Code FTS1801149
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W ND

Luminaire Flux	4388.60 lm	Luminaire Power	54.00 W	Efficacy	81.27 lm/W	Efficiency	100.00%
Sources Flux	4388.60 lm	Maximum value	1117.04 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	188 mm	Width	188 mm	Height	238 mm
Rectangular Luminous Area		Length	177 mm	Width	177 mm	Height	0 mm
Horizontal Luminous Area		0.031329 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007579 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4388.60 lm	
LED Flux=5451lm LED Power=50W Eff=81% EfcLed=109lm/W EfcLum=81lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	95	100	100	100	D DIN 5040	A60	
F UTE	1.00	A			B NBN	BZ 1	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.53	1.07	1.60	2.14	2.67	OC	0.54	1.08	1.62	2.16	2.69
OB	0.53	1.07	1.60	2.14	2.67	OD	0.54	1.08	1.62	2.16	2.69

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4902.24	4803.07	4171.05	3110.08	1140.43	185.76	7.57	4.40	3.87	2.99
OB	4902.24	4803.07	4171.05	3110.08	1140.43	185.76	7.57	4.40	3.87	2.99
OC	4902.24	4795.69	4185.58	3152.13	1173.33	197.69	7.74	4.41	3.73	2.61
OD	4902.24	4795.69	4185.58	3152.13	1173.33	197.69	7.74	4.41	3.73	2.61



H[m]	D[m]	Max lux	Med lux	Alpha=28.1°+28.1°	G=0.0
1.00	1.07	4902	2826		
2.00	2.14	1226	707		
3.00	3.21	545	314		
4.00	4.27	306	177		
5.00	5.34	196	113		

H[m]	D[m]	Max lux	Med lux	Beta=28.3°+28.3°	G=0.0
1.00	1.08	4902	2826		
2.00	2.16	1226	707		
3.00	3.23	545	314		
4.00	4.31	306	177		
5.00	5.39	196	113		