

## Luminaire


Code BZ02405IN0+BZ05904  
 Name A.39 S/C SHARP REFR.DIR 1184 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 1184 NRO

## Measurement

Code FTS2103019  
 Name A.39 S/C SHARP REFR.DIR 1184 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 1184 NRO

Luminaire Flux	4185 lm	Luminaire Power	35.0 W	Efficacy	119.583 lm/W	Efficiency	100.00%
Source Flux	4185 lm	Maximum value	1168.42 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1180 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.041300 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009991 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4185 lm	
LED Flux=5140lm LED Power=31W Eff=81% EfcLed=165lm/W EfcLum=120lm/W CCT=5000 Ra=90 SDCM=3 L70(9K)=50000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

1184mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

