

## Luminaire

Code BZ04204IN0+BZ06101  
 Name A.39 S SHARP REFR.D+I 2368 WIN N/D NRO + A.39 S/C SHARP REFR KIT LOUVRES 2368 BCO

## Measurement

Code FTS2103085-A  
 Name A.39 S SHARP REFR.D+I 2368 WIN N/D NRO + A.39 S/C SHARP REFR KIT LOUVRES 2368 BCO

|                            |          |                         |               |                             |               |                         |                    |
|----------------------------|----------|-------------------------|---------------|-----------------------------|---------------|-------------------------|--------------------|
| Luminaire Flux             | 13800 lm | Luminaire Power         | 120.0 W       | Efficacy                    | 115.002 lm/W  | Efficiency              | 100.00%            |
| Source Flux                | 13800 lm | Maximum value           | 784.48 cd/klm | Position                    | C=0.00 G=0.00 | CG                      | Double Symmetrical |
| Rectangular Luminaire      |          | Length                  | 2368 mm       | Width                       | 45 mm         | Height                  | 85 mm              |
| Rectangular Luminous Area  |          | Length                  | 2363 mm       | Width                       | 35 mm         | Height                  | 0 mm               |
| Horizontal Luminous Area   |          | 0.082705 m <sup>2</sup> |               | Emitting area on Plane 180° |               | 0.000000 m <sup>2</sup> |                    |
| Emitting area on Plane 0°  |          | 0.000000 m <sup>2</sup> |               | Emitting area on Plane 270° |               | 0.000000 m <sup>2</sup> |                    |
| Emitting area on Plane 90° |          | 0.000000 m <sup>2</sup> |               | Glare area at 76°           |               | 0.020008 m <sup>2</sup> |                    |
| Coordinate system          |          | CG                      |               | Symmetry Type               |               | Double Symmetrical      |                    |
| Date                       |          | 16-05-2022              |               | Maximum Gamma Angle         |               | 180                     |                    |
| Measurement Distance       |          | 0.00                    |               | Measurement Flux            |               | 13800 lm                |                    |


LED Flux=15607lm LED Power=104W Eff=88% EfcLed=151lm/W EfcLum=115lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 67 100  
 F UTE --

D DIN 5040  
 B NBN

B61  
 BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 32.86 %

DLOR 67.14 %

RN 32.86 %

