

Luminaire

Code BZ05405IN0+BZ06101
 Name A.39 S SHARP REFR.D+I 2368 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 2368 BCO

Measurement

Code FTS2103085-A
 Name A.39 S SHARP REFR.D+I 2368 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 2368 BCO

Luminaire Flux	13800 lm	Luminaire Power	120.0 W	Efficacy	115.002 lm/W	Efficiency	100.00%
Source Flux	13800 lm	Maximum value	784.48 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2363 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.082705 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.020008 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		13800 lm	


LED Flux=15607lm LED Power=104W Eff=88% EfcLed=151lm/W EfcLum=115lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 67 100
 F UTE --

D DIN 5040
 B NBN

B61
 BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 32.86 %

DLOR 67.14 %

RN 32.86 %

