

Luminaire

Code CA32104
Name GOPLE 80 S / TRK16 48V 4000K FL NRO

Measurerm.

Code FTS2200069
Name GOPLE 80 S / TRK16 48V 4000K FL NRO

Luminaire Flux	1814 lm	Luminaire Power	23.0 W	Efficacy	78.887 lm/W	Efficiency	100.00%
Source Flux	1814 lm	Maximum value	5833.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		01-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1814 lm	

LED Flux=2473lm LED Power=22W Eff=73% EfcLed=114lm/W EfcLum=79lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 99 100 100 100 100
F UTE --

D DIN 5040
B NBN

A60
BZ 1


Diam=77mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code CA32104
Name GOPLE 80 S / TRK16 48V 4000K FL NRO

Measurerm.


Code FTS2200069
Name GOPLE 80 S / TRK16 48V 4000K FL NRO

Luminaire Flux	1814 lm	Luminaire Power	23.0 W	Efficacy	78.887 lm/W	Efficiency	100.00%
Source Flux	1814 lm	Maximum value	5833.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	77 mm	Height	150 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		01-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1814 lm	
LED Flux=2473lm LED Power=22W Eff=73% EfcLed=114lm/W EfcLum=79lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.19	0.38	0.58	0.77	0.96	OC	0.19	0.38	0.58	0.77	0.96
OB	0.19	0.38	0.58	0.77	0.96	OD	0.19	0.38	0.58	0.77	0.96

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	10584.36	9381.10	2480.50	587.86	17.01	7.31	4.25	2.88	1.56	0.56
OB	10584.36	9381.10	2480.50	587.86	17.01	7.31	4.25	2.88	1.56	0.56
OC	10584.36	9381.10	2480.50	587.86	17.01	7.31	4.25	2.88	1.56	0.56
OD	10584.36	9381.10	2480.50	587.86	17.01	7.31	4.25	2.88	1.56	0.56



H[m]	D[m]	Max lux	Med lux	Alpha=10.9°+10.9°	G=0.0
1.00	0.38	10584	6794		
2.00	0.77	2646	1699		
3.00	1.15	1176	755		
4.00	1.53	662	425		
5.00	1.92	423	272		