

Luminaire

Code BZ04304+BZ06201
 Name A.39 S SHARP REFR.D+I 2960 830 N/D NRO + KIT LOUVRES 2960 BCO

Measurem.

Code FTS2102109-A
 Name A.39 S SHARP REFR.D+I 2960 830 N/D NRO + KIT LOUVRES 2960 BCO

Luminaire Flux	20810 lm	Luminaire Power	153.0 W	Efficacy	136.013 lm/W	Efficiency	100.00%
Source Flux	20810 lm	Maximum value	651.95 cd/klm	Position	C=80.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.024978 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		02-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		20810 lm	


LED Flux=23820lm LED Power=132W Eff=87% EfcLed=180lm/W EfcLum=136lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 93 97 99 61 100
 F UTE 0.61 A + 0.39 T

D DIN 5040
 B NBN

B61
 BZ 1

2960mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 39.40 %
 DLOR 60.60 %
 RN 39.40 %

