

Luminaire

Code BZ05504+BZ06204
 Name A.39 S SHARP REFR.D+I 2960 830 DALINRO + KIT LOUVRES 2960 NRO

Measurement

Code FTS2102115-A
 Name A.39 S SHARP REFR.D+I 2960 830 DALINRO + KIT LOUVRES 2960 NRO

Luminaire Flux	19410 lm	Luminaire Power	153.0 W	Efficacy	126.863 lm/W	Efficiency	100.00%
Source Flux	19410 lm	Maximum value	676.02 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.024978 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		02-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		19410 lm	


LED Flux=23820lm LED Power=132W Eff=81% EfcLed=180lm/W EfcLum=127lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 98 100 100 58 100
 F UTE --

D DIN 5040
 B NBN

C61
 BZ 1

2960mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 42.24 %

DLOR 57.76 %

RN 42.24 %

