

Luminaire


Code BZ02304+BZ05901
 Name A.39 S/C SHARP REFR.DIR 1184 840 DALINRO + KIT LOUVRES 1184 BCO

Measurement

Code FTS2102121-A
 Name A.39 S/C SHARP REFR.DIR 1184 840 DALINRO + KIT LOUVRES 1184 BCO

| | | | | | | | |
|---|------------------|-----------------|----------------|-----------------------------|----------------|--------------------|--------------------|
| Luminaire Flux | 5311 lm | Luminaire Power | 35.0 W | Efficacy | 151.743 lm/W | Efficiency | 100.00% |
| Source Flux | 5311 lm | Maximum value | 1075.90 cd/klm | Position | C=80.00 G=1.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 45 mm | Height | 85 mm |
| Rectangular Luminous Area | | Length | 1180 mm | Width | 35 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.041300 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.009991 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 08-11-2023 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 5311 lm | |
| LED Flux=5867lm LED Power=31W Eff=91% EfcLed=188lm/W EfcLum=152lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 93 97 99 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 A | | | B NBN | BZ 1 | | |

1184mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

