

## Luminaire

Code BZ02601+BZ06001  
 Name A.39 S/C SHARP REFR.DIR 1482 840 DALIBCO + KIT LOUVRES 1482 BCO

## Measurement

Code FTS2102133-A  
 Name A.39 S/C SHARP REFR.DIR 1482 840 DALIBCO + KIT LOUVRES 1482 BCO

Luminaire Flux	6638 lm	Luminaire Power	43.0 W	Efficacy	154.372 lm/W	Efficiency	100.00%
Source Flux	6638 lm	Maximum value	1075.90 cd/klm	Position	C=80.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1480 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1475 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.051625 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.012489 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6638 lm	
LED Flux=7334lm LED Power=39W Eff=91% EfcLed=188lm/W EfcLum=154lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	93 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

1480mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



