


Luminaire

Code TC53204+AP90200
 Name GOPLE 60 PENDANT TRK12 940 FL BLACK + LENS FOR ELLIPTICAL EMISSION

Measurement

Code FTS2200211
 Name GOPLE 60 PENDANT TRK12 940 FL BLACK + LENS FOR ELLIPTICAL EMISSION

Luminaire Flux	364 lm	Luminaire Power	10.0 W	Efficacy	36.445 lm/W	Efficiency	100.00%
Source Flux	364 lm	Maximum value	3396.08 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area			0.000962 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000233 m2
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		364 lm	
LED Flux=929lm LED Power=7.9W Eff=39% EfcLed=117lm/W EfcLum=36lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	96 99 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		



Luminaire

Code TC53204+AP90200
Name GOPLE 60 PENDANT TRK12 940 FL BLACK + LENS FOR ELLIPTICAL EMISSION

Measurerm.

Code FTS2200211
Name GOPLE 60 PENDANT TRK12 940 FL BLACK + LENS FOR ELLIPTICAL EMISSION

Luminaire Flux	364 lm	Luminaire Power	10.0 W	Efficacy	36.445 lm/W	Efficiency	100.00%
Source Flux	364 lm	Maximum value	3396.08 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area		0.000962 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000233 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-09-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		364 lm	


LED Flux=929lm LED Power=7.9W Eff=39% EfcLed=117lm/W EfcLum=36lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h

C.I.E.	96 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.19	0.37	0.56	0.74	0.93	OC	0.32	0.64	0.96	1.28	1.60
OB	0.19	0.37	0.56	0.74	0.93	OD	0.32	0.64	0.96	1.28	1.60

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1237.70	1047.30	339.46	78.04	12.47	4.37	2.15	1.35	0.87	0.29
OB	1237.70	1047.30	339.46	78.04	12.47	4.37	2.15	1.35	0.87	0.29
OC	1237.70	1160.37	744.04	348.39	120.27	29.87	15.31	10.29	2.24	0.28
OD	1237.70	1160.37	744.04	348.39	120.27	29.87	15.31	10.29	2.24	0.28



H[m]	D[m]	Max lux	Med lux	Alpha=10.5°+10.5°	G=0.0
1.00	0.37	1238	749		
2.00	0.74	309	187		
3.00	1.11	138	83		
4.00	1.48	77	47		
5.00	1.85	50	30		

H[m]	D[m]	Max lux	Med lux	Beta=17.8°+17.8°	G=0.0
1.00	0.64	1238	749		
2.00	1.28	309	187		
3.00	1.93	138	83		
4.00	2.57	77	47		
5.00	3.21	50	30		