

Luminaire

Code CE14405IN0+BZ07204
 Name SHARP REFRACTIVE TRIM 8 UNIT W1 WF SIL + SHARP REFRACTIVE KIT LOUVRES 2 UNIT NRO

Measurement

Code FTS2200296-A
 Name SHARP REFRACTIVE TRIM 8 UNIT W1 WF SIL + SHARP REFRACTIVE KIT LOUVRES 2 UNIT NRO

Luminaire Flux	2126 lm	Luminaire Power	16.0 W	Efficacy	132.888 lm/W	Efficiency	100.00%
Source Flux	2126 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	312 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	280 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.009800 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002371 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-02-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2126 lm	
LED Flux=2642lm LED Power=16W Eff=80% EfcLed=165lm/W EfcLum=133lm/W CCT=5000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1



