

## Luminaire

Code CM100105  
Name A.39 MICRO REFR.1184 DIR 930 DALI NR/GR

## Measurement

Code FTS2400076  
Name A.39 MICRO REFR.1184 DIR 930 DALI NR/GR

Luminaire Flux	2806 lm	Luminaire Power	19.0 W	Efficacy	147.684 lm/W	Efficiency	100.00%
Source Flux	2806 lm	Maximum value	922.70 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1088 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.036992 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.008949 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2806 lm	


LED Flux=3322lm LED Power=18W Eff=84% EfcLed=190lm/W EfcLum=148lm/W CCT=3000K Ra=90 SDCM=3 L70(17k)=102000h

C.I.E. 100 100 100 100 100  
F UTE --

D DIN 5040  
B NBN

A60  
BZ 1

1184mm x 45mm



Sempiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 0.00 %  
DLOR 100.00 %  
RN 0.00 %

