

Luminaire

Code BW41004+AP91300
 Name VECTOR SPOT 55 CHANNEL 14W 3000K SP BLK + SOFT FILTER

Measurement

Code FTS2300091-A
 Name VECTOR SPOT 55 CHANNEL 14W 3000K SP BLK + SOFT FILTER

Luminaire Flux	1083 lm	Luminaire Power	14.0 W	Efficacy	77.357 lm/W	Efficiency	100.00%
Source Flux	1083 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000438 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		11-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1083 lm	
LED Flux=2033lm LED Power=14W Eff=53% EfcLed=145lm/W EfcLum=77lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Diam=55mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code BW41004+AP91300
Name VECTOR SPOT 55 CHANNEL 14W 3000K SP BLK + SOFT FILTER

Measurerm.


Code FTS2300091-A
Name VECTOR SPOT 55 CHANNEL 14W 3000K SP BLK + SOFT FILTER

Luminaire Flux	1083 lm	Luminaire Power	14.0 W	Efficacy	77.357 lm/W	Efficiency	100.00%
Source Flux	1083 lm	Maximum value	4480.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	48 mm	Height	0 mm		
Horizontal Luminous Area		0.001810 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000438 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		11-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1083 lm	
LED Flux=2033lm LED Power=14W Eff=53% EfcLed=145lm/W EfcLum=77lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.20	0.41	0.61	0.82	1.02	OC	0.20	0.41	0.61	0.82	1.02
OB	0.20	0.41	0.61	0.82	1.02	OD	0.20	0.41	0.61	0.82	1.02

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4852.75	4212.20	1627.64	400.28	75.62	16.21	6.12	4.50	2.89	0.79
OB	4852.75	4212.20	1627.64	400.28	75.62	16.21	6.12	4.50	2.89	0.79
OC	4852.75	4212.20	1627.64	400.28	75.62	16.21	6.12	4.50	2.89	0.79
OD	4852.75	4212.20	1627.64	400.28	75.62	16.21	6.12	4.50	2.89	0.79



H[m]	D[m]	Max lux	Med lux	Alpha=11.6°+11.6°	G=0.0
1.00	0.41	4853	3024		
2.00	0.82	1213	756		
3.00	1.23	539	336		
4.00	1.64	303	189		
5.00	2.04	194	121		