

Luminaire

Code BT06118_N
Name VECTOR 75 3P DALI8 TW SP BCP

Measurerm.

Code FTS2300002
Name VECTOR 75 3P DALI8 TW SP BCP

Luminaire Flux	1874 lm	Luminaire Power	26.0 W	Efficacy	72.070 lm/W	Efficiency	100.00%
Source Flux	1874 lm	Maximum value	9349.16 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	75 mm	Height	200 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area		0.002827 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000684 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		15-12-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1874 lm	
LED Flux=2437lm LED Power=22W Eff=77% EfcLed=111lm/W EfcLum=72lm/W CCT=6500K Ra=90 R9=50 SDCM=3 L70(9K)=50000h							
C.I.E.	100	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

Diam=75mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



