

## Luminaire

Code CE13005+BZ07101  
 Name SHARP REFRACTIVE TRIM 4 UNIT 2700K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

## Measurement


Code FTS2200267  
 Name SHARP REFRACTIVE TRIM 4 UNIT 2700K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

Luminaire Flux	1131 lm	Luminaire Power	8.0 W	Efficacy	141.366 lm/W	Efficiency	100.00%
Source Flux	1131 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire	Length	164 mm	Width	55 mm	Height	55 mm	55 mm
Rectangular Luminous Area	Length	140 mm	Width	35 mm	Height	0 mm	0 mm
Horizontal Luminous Area	0.004900 m <sup>2</sup>	Emitting area on Plane 180°	0.000000 m <sup>2</sup>	Emitting area on Plane 270°	0.000000 m <sup>2</sup>	Emitting area on Plane 90°	0.001185 m <sup>2</sup>
Coordinate system	CG	Date	04-10-2022	Symmetry Type	Double Symmetrical	Measurement Distance	180
Measurement Distance	0.00	Maximum Gamma Angle	180	Measurement Flux	1131 lm		

LED Flux=1249lm LED Power=8W Eff=91% EfcLed=156lm/W EfcLum=141lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	92 97 99 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

164mm x 55mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

