

Luminaire


Code CE13001+BZ07104
 Name SHARP REFRACTIVE TRIM 4 UNIT 2700K WF BCO + SHARP REFRACTIVE KIT LOUVRES 1 UNIT NRO

Measurement

Code FTS2200283
 Name SHARP REFRACTIVE TRIM 4 UNIT 2700K WF BCO + SHARP REFRACTIVE KIT LOUVRES 1 UNIT NRO

Luminaire Flux	1005 lm	Luminaire Power	8.0 W	Efficacy	125.670 lm/W	Efficiency	100.00%
Source Flux	1005 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	164 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	140 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.004900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001185 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		04-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1005 lm	
LED Flux=1249lm LED Power=8W Eff=80% EfcLed=156lm/W EfcLum=126lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

164mm x 55mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

