

Luminaire

Code CE15004+BZ07304

Name SHARP REFRACTIVE TRIM 12 UNIT 2700K WF NRO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT NRO


Measurement

Code FTS2200285

Name SHARP REFRACTIVE TRIM 12 UNIT 2700K WF NRO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT NRO

Luminaire Flux	3016 lm	Luminaire Power	24.0 W	Efficacy	125.670 lm/W	Efficiency	100.00%
Source Flux	3016 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	460 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	420 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.014700 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003556 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		04-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3016 lm	
LED Flux=3748lm LED Power=24W Eff=80% EfcLed=156lm/W EfcLum=126lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

460mm x 55mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

