

## Luminaire

Code FW10001  
Name DIFFUSED LINEAR 1200 FUNIVIA 927 BCO

## Measurement

Code FTS2300040-A  
Name DIFFUSED LINEAR 1200 FUNIVIA 927 BCO


Luminaire Flux	2241 lm	Luminaire Power	26.0 W	Efficacy	86.192 lm/W	Efficiency	100.00%
Source Flux	2241 lm	Maximum value	350.51 cd/klm	Position	C=60.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1200 mm	Width	20 mm	Height	20 mm
Rectangular Luminous Area		Length	1176 mm	Width	18 mm	Height	0 mm
Horizontal Luminous Area		0.021168 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.005121 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		22-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2241 lm	

LED Flux=3523lm LED Power=24W Eff=64% EfcLed=149lm/W EfcLum=86lm/W CCT=2700K Ra=80 SDCM=2 L70(19k)=116750h

C.I.E. 47 79 96 100 100  
F UTE 1.00 E

D DIN 5040  
B NBN

A30  
BZ 5 / 1.25 / BZ 4



## Luminaire

Code FW10001  
Name DIFFUSED LINEAR 1200 FUNIVIA 927 BCO

## Measurment.


Code FTS2300040-A  
Name DIFFUSED LINEAR 1200 FUNIVIA 927 BCO

Luminaire Flux	2241 lm	Luminaire Power	26.0 W	Efficacy	86.192 lm/W	Efficiency	100.00%
Source Flux	2241 lm	Maximum value	350.51 cd/klm	Position	C=60.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1200 mm	Width	20 mm	Height	20 mm
Rectangular Luminous Area		Length	1176 mm	Width	18 mm	Height	0 mm
Horizontal Luminous Area		0.021168 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005121 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		22-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2241 lm	
LED Flux=3523lm LED Power=24W Eff=64% EfcLed=149lm/W EfcLum=86lm/W CCT=2700K Ra=80 SDCM=2 L70(19k)=116750h							
C.I.E.	47 79 96 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 5 / 1.25 / BZ 4		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.48	2.96	4.43	5.91	7.39	OC	1.54	3.07	4.61	6.15	7.68
OB	1.48	2.96	4.43	5.91	7.39	OD	1.54	3.07	4.61	6.15	7.68

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	785.46	781.75	752.23	695.93	616.87	518.77	403.12	275.59	144.35	32.31
OB	785.46	781.75	752.23	695.93	616.87	518.77	403.12	275.59	144.35	32.31
OC	785.46	782.22	754.79	702.09	626.34	530.05	416.10	288.98	153.13	39.06
OD	785.46	782.22	754.79	702.09	626.34	530.05	416.10	288.98	153.13	39.06



H[m]	D[m]	Max lux	Med lux	Alpha=55.9°+55.9°	G=0.0
1.00	2.96	785	188		
2.00	5.91	196	47		
3.00	8.87	87	21		
4.00	11.82	49	12		
5.00	14.78	31	8		

H[m]	D[m]	Max lux	Med lux	Beta=56.9°+56.9°	G=0.0
1.00	3.07	785	188		
2.00	6.15	196	47		
3.00	9.22	87	21		
4.00	12.29	49	12		
5.00	15.36	31	8		