

Luminaire


Code CM200101
Name A.39 MICRO REFR 1480 DIR 930 DALI BC/BC

Measurement

Code FTS2400077
Name A.39 MICRO REFR 1480 DIR 930 DALI BC/BC

Luminaire Flux	3943 lm	Luminaire Power	24.0 W	Efficacy	164.292 lm/W	Efficiency	100.00%
Source Flux	3943 lm	Maximum value	882.38 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1482 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1360 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.046240 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.011186 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3943 lm	
LED Flux=4152lm LED Power=22W Eff=95% EfcLed=190lm/W EfcLum=164lm/W CCT=3000K Ra=90 SDCM=3 L70(17k)=102000h							
C.I.E.	93 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

1482mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

