


Luminaire

Code CM401105
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/GR

Measurement

Code FTS2400096
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/GR

Luminaire Flux	5612 lm	Luminaire Power	38.0 W	Efficacy	147.684 lm/W	Efficiency	100.00%
Source Flux	5612 lm	Maximum value	922.70 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2176 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.073984 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.017898 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		25-03-2024		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	5612 lm		
LED Flux=6643lm LED Power=35W Eff=84% EfcLed=190lm/W EfcLum=148lm/W CCT=4000K Ra=90 SDCM=3 L70(17k)=102000h							
C.I.E.	100	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



Luminaire

Code CM401105
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/GR

Measurerm.


Code FTS2400096
Name A.39 MICRO REFR.2368 DIR 940 DALI NR/GR

Luminaire Flux	5612 lm	Luminaire Power	38.0 W	Efficacy	147.684 lm/W	Efficiency	100.00%
Source Flux	5612 lm	Maximum value	922.70 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2176 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.073984 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.017898 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5612 lm	
LED Flux=6643lm LED Power=35W Eff=84% EfcLed=190lm/W EfcLum=148lm/W CCT=4000K Ra=90 SDCM=3 L70(17k)=102000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.64	1.28	1.92	2.56	3.20	OC	0.64	1.28	1.92	2.56	3.20
OB	0.64	1.28	1.92	2.56	3.20	OD	0.64	1.28	1.92	2.56	3.20

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	5175.17	5154.87	5060.35	4996.33	1432.85	46.83	13.05	3.21	2.03	1.26
OB	5175.17	5154.87	5060.35	4996.33	1432.85	46.83	13.05	3.21	2.03	1.26
OC	5175.17	5156.27	5075.64	4979.90	1447.00	50.12	15.00	3.55	2.07	1.32
OD	5175.17	5156.27	5075.64	4979.90	1447.00	50.12	15.00	3.55	2.07	1.32



H[m]	D[m]	Max lux	Med lux	Alpha=32.6°+32.6°	G=0.0
1.00	1.28	5177	3124		
2.00	2.56	1294	781		
3.00	3.84	575	347		
4.00	5.12	324	195		
5.00	6.40	207	125		

H[m]	D[m]	Max lux	Med lux	Beta=32.6°+32.6°	G=0.0
1.00	1.28	5177	3124		
2.00	2.56	1294	781		
3.00	3.84	575	347		
4.00	5.12	324	195		
5.00	6.40	207	125		