

Luminaire


Code CM211104
Name A.39 MICRO REFR.1480 DI/IN 940 DAL NR/NR

Measurement

Code FTS2400102
Name A.39 MICRO REFR.1480 DI/IN 940 DAL NR/NR

Luminaire Flux	6180 lm	Luminaire Power	44.0 W	Efficacy	140.455 lm/W	Efficiency	100.00%
Source Flux	6180 lm	Maximum value	523.76 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1482 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1360 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.046240 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.011186 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		25-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6180 lm	
LED Flux=7460lm LED Power=39W Eff=83% EfcLed=189lm/W EfcLum=140lm/W CCT=4000K Ra=90 SDCM=3 L70(17k)=102000h							
C.I.E.	100 100 100 57 100			D DIN 5040	C61		
F UTE	--			B NBN	BZ 1		

1482mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 43.23 %

DLOR 56.77 %

RN 43.23 %

