

## Luminaire

Code A006400  
Name ONFALE T PICCOLO

## Measurerm.

Code FTS2200002  
Name ONFALE T PICCOLO

Luminaire Flux	363 lm	Luminaire Power	5.0 W	Efficacy	72.530 lm/W	Efficiency	77.16%
Source Flux	470 lm	Maximum value	105.65 cd/klm	Position	C=0.00 G=179.00	CG	Rotosymmetrical
Round Luminaire		Diam.	100 mm	Height	133 mm		
Round Luminous Area		Diam.	100 mm	Height	133 mm		
Horizontal Luminous Area		0.007854 m <sup>2</sup>		Emitting area on Plane 180°		0.013300 m <sup>2</sup>	
Emitting area on Plane 0°		0.013300 m <sup>2</sup>		Emitting area on Plane 270°		0.013300 m <sup>2</sup>	
Emitting area on Plane 90°		0.013300 m <sup>2</sup>		Glare area at 76°		0.014805 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		02-02-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		470 lm	

Lamping=LED 1x5W (E14) CCT=2700K CRI=80

C.I.E. 20 40 67 33 77  
F UTE 0.26 J + 0.51 T

D DIN 5040  
B NBN

D12  
BZ 9 / 1.5 / BZ 10

Diam=100mm



Semipiani C

180.0 ——— 0.0

ULOR 51.32 %

DLOR 25.84 %

RN 66.51 %

